

BR1: DIODES, INC. HD06
D1: CENTRAL SEMICONDUCTOR CMR1U-06M
D2 D3: DIODES INC. BAV20W

-
- 90V
TO 265V
AC
- L1
3.3mH
- R20, 10k
- R21, 10k
- L2, 3.3mH
- C1
33nF
- BR1
- L1
3.3mH
- C3
68nF
- R1
750Ω
- C2
22nF
- R3
499k
- R4
499k
- R5
3.48k
- R7
100k
- R8
100k
- D2
20Ω
- C4
4.7pF
- C5
10μF
- R13
10k
- R4
100k
- R15
4.99k
- R16
20Ω
- D1
- M1
- RS
0.3Ω
- C8
2.2nF
- C9
4.7μF
- C6
0.1μF
- C7
0.1μF
- C10
1500μF
- D4
- Z1
- Z2
- 1A
- 4W
LED
POWER
- 3799 TA03
- LT3799
- VIN
- VIN_SENSE
- VREF
- CTRL3
- CTRL2
- CTRL1
- GATE
- SENSE
- INTVCC
- GND
- FAULT
- CT
- COMP+
- COMP-
- DCM
- FB
- 20:5:1
- PFC

Universal Input TRIAC Dimmable 14W LED Driver

