
Cypress Component Catalog
Analog
ADC
Delta Sigma ADC [v3.20]
SAR ADC [v3.0]
Sequencing SAR ADC [v2.0]
Amplifiers
Inverting PGA [v2.0]
Opamp [v1.90]
PGA [v2.0]
TIA [v2.0]
Analog MUX
Analog Hardware Mux (GPIO) [v1.50]
Analog Mux [v1.80]
Analog Mux Sequencer [v1.80]
Analog Virtual Mux [v1.0]
Comparators
Comparator [v2.0]
Comparator SC/CT Block [v1.0]
Scanning Comparator [v1.10]
DAC
Current DAC (8-bit) [v2.0]
Dithered VDAC (9 to12 bits) [v2.10]
Voltage DAC (8-bit) [v1.90]
Waveform DAC (8-bit) [v2.10]

- Manual Routing
  - Mux Constraint [v1.50]
  - Net Constraint [v1.50]
  - Net Tie [v1.50]
  - Resource Reserve [v1.50]
  - Stay Awake [v1.50]
  - Terminal Reserve [v1.50]
- Mixer [v2.0]
- Sample/Track and Hold [v1.40]
- VRef [v1.60]

- CapSense
  - CapSense_CSD [v3.50]

- Communications
  - CAN Controller Macro [v3.0]
  - File System
    - emFile SPI Mode [v1.20]
  - I2C
    - EZI2C Slave [v2.0]
    - I2C [v3.50]
    - I2C Master (Fixed Function) [v3.50]
    - I2C Master (UDB) [v3.50]
    - I2C Slave (Fixed Function) [v3.50]
    - I2C Slave (UDB) [v3.50]

- I2S
  - I2S Rx and Tx [v2.70]
  - I2S Rx Only [v2.70]
  - I2S Tx Only [v2.70]
- LIN [v3.30]
- LIN Slave Macro [v3.30]
- MDIO Interface
  - MDIO Interface (Advanced) [v1.20]
  - MDIO Interface (Basic) [v1.20]
  - MDIO Interface [v1.20]
- SMBus/PMBus Slave
  - PMBus Slave [v5.10]
  - SMBus Slave [v5.10]
  - SMBus/PMBus Slave [v5.10]
- Software Transmit UART [v1.50]
- SPDIF Transmitter [v1.20]
- SPI
  - SPI Master [v2.50]
  - SPI Master Bidirectional mode Macro [v2.50]
  - SPI Master Full Duplex mode Macro [v2.50]
  - SPI Slave [v2.70]
  - SPI Slave Bidirectional mode Macro [v2.70]
  - SPI Slave Full Duplex mode Macro [v2.70]
  - SPI Slave Multislave Mode macro [v2.70]
- UART [v2.50]

- UART [v2.50]
- USB
  - USBFS [v3.0]
  - USBMIDI [v3.0]
  - USBUART (CDC Interface) [v3.0]
- Digital
  - Functions
    - Counter [v3.0]
    - CRC [v2.40]
    - PrISM [v2.20]
    - PRS [v2.40]
    - PWM [v3.30]
    - Quadrature Decoder [v3.0]
    - Shift Register [v2.30]
    - Timer [v2.70]
  - Logic
    - And [v1.0]
    - Bufoe [v1.10]
    - D Flip Flop [v1.30]
    - D Flip Flop w/ Enable [v1.0]
    - De-Multiplexer [v1.10]
    - Digital Constant [v1.0]
    - Logic High '1' [v1.0]
    - Logic Low '0' [v1.0]
    - Lookup Table [v1.50]
    - Multiplexer [v1.10]
    - Nand [v1.0]
    - Nor [v1.0]

- Or [v1.0]
- SR Flip Flop [v1.0]
- Toggle Flip Flop [v1.0]
- Virtual Mux [v1.0]
- Xnor [v1.0]
- Xor [v1.0]
- Registers
  - Control Register [v1.80]
  - Status Register [v1.90]
- Utility
  - Basic Counter [v1.0]
  - Debouncer [v1.0]
  - Digital Comparator [v1.0]
  - Down Counter (7-bit) [v1.0]
  - Edge Detector [v1.0]
  - Frequency Divider [v1.0]
  - Glitch Filter [v2.0]
  - Pulse Converter [v1.0]
  - Sync [v1.0]
  - UDB Clock Enable [v1.0]
- Display
  - 4 Digit 7-Segment LED Driver [v1.10]
  - Character LCD [v2.20]
  - Character LCD with I2C interface [v1.20]
  - Graphic LCD 8-bit Parallel Interface Macro [v1.70]
  - Graphic LCD 16-bit Parallel Interface Macro [v1.70]
  - Graphic LCD Controller [v1.70]
  - Graphic LCD Controller Macro [v1.70]

- Graphic LCD Parallel Interface [v1.70]
- LED Segment and Matrix Driver [v1.10]
- ResistiveTouch [v2.0]
- Segment LCD - Static [v2.30]
- Segment LCD [v3.40]

Filters

- Digital Filter Block (DFB) Assembler [v1.40]
- Filter [v2.30]

Ports and Pins

- Analog Pin [v2.20]
- Digital Bidirectional Pin [v2.20]
- Digital Input Pin [v2.20]
- Digital Output Pin [v2.20]

Power Supervision

- Power Monitor - 8 Rails [v1.60]
- Power Monitor - 16 Rails [v1.60]
- Power Monitor - 32 Rails [v1.60]
- Power Monitor [v1.60]
- Trim and Margin - 8 Rails [v3.0]
- Trim and Margin [v3.0]
- Voltage Fault Detector - 8 Rails [v3.0]
- Voltage Fault Detector - 16 Rails [v3.0]
- Voltage Fault Detector - 32 Rails [v3.0]
- Voltage Fault Detector [v3.0]
- Voltage Sequencer - 8 Rails [v3.40]
- Voltage Sequencer - 16 Rails [v3.40]
- Voltage Sequencer - 32 Rails [v3.40]
- Voltage Sequencer [v3.40]

- System
  - Boost Converter [v5.0]
  - Bootloadable [v1.50]
  - Bootloader [v1.50]
  - Clock [v2.20]
  - Die Temperature [v2.0]
  - DMA [v1.70]
  - EEPROM [v3.0]
  - Emulated EEPROM [v1.10]
  - External Memory Interface
    - Asynchronous External Memory Interface [v1.30]
    - Custom External Memory Interface [v1.30]
    - Synchronous External Memory Interface [v1.30]
  - Global Signal Reference [v2.0]
  - ILO Trim [v2.0]
  - Interrupt [v1.70]
  - RTC [v2.0]
  - SleepTimer [v3.20]
- Thermal Management
  - Fan Controller [v4.0]
  - RTD Calculator [v1.20]
  - Thermistor Calculator [v1.20]
  - Thermocouple Calculator [v1.20]
  - TMP05 Interface Macro [v1.10]